


J600P - ACO PITLOK® SCEC (SL1) - concrete pit & steel lid





Cable pit - full body





Cable pit - split body





- Key

 ① Clear working dimension at pit base
 ② Clear working dimension at pit opening
 ③ Clear working dimension beneath lid rebate

J600P - ACO PITLOK® SCEC (SL1) - concrete pit & steel lid

Cable pit and riser

Description	Part No	Depth mm	Weight kg
J600P - ACO PitLok® - concrete pit & steel lid - full body	142245	910	495
J600P - ACO PitLok® - concrete pit & steel lid - split body	142246	910	488

Accessories & ancillary items

Description	Part	Weight
	No	kg
Lid Lifting Tool	142232	0.5
ID Plates	On Enquiry	N/A
Route Marker Plates	On Enquiry	N/A
SCEC (SL3) Padlocks	On Enquiry	0.5
Swing Arm	On Enquiry	1
SCEC (SL1) approved precast concrete riser	On Enquiry	Variable

Specifications

General

The cable pit shall be ACO J600P PITLOK SCEC (SL1) - concrete pit & steel lid - full* / split* body as supplied by ACO Pty Ltd. or equal approved.

The pit is fully tested and assessed by Security Services who conduct tests on behalf of SCEC. SCEC have subsequently endorsed the lids and pits for the 'Protection of Classified Material'. This is contingent on the use of SCEC (SL3) padlocks to secure the lids.

Materials

The pit body shall be manufactured from steel reinforced cement concrete with:

Compressive strength:

J

40MPa

The nominal clear opening shall be 535mm x 535mm. Units shall be manufactured with an internal depth of 820mm.

Lid

The pit shall be covered with a SCEC (SL1) approved tamper evident locking steel lid.

Installation

The cable pit shall be installed in accordance with the manufacturer's installation instructions and recommendations.

* delete as applicable

ACO Pty Ltd Australia

Ph: 1300 765 226 www.acoaus.com.au sales@acoaus.com.au



