



**Parts Table**

Enclosures/Lids		
Descriptions/dimensions	Part No.	Weight (kg)
EzyBrixx 1350mm x 600mm x (900mm deep) pit	142651	66
EzyBrixx 1350mm x 600mm x (900mm deep) pit with base	142652	76
EzyBrixx 1300mm x 600mm base (supplied loose)	142655	10
EzyBrixx 1350mm x 600mm steel (2 part) bolt locking lid - Class B	142656	80
EzyBrixx 1350mm x 600mm steel (2 part) bolt locking lid - Class D	142657	95
EzyBrixx Access Cover - 1350 x 600 Class B Tilemate infill	82628	39.2
EzyBrixx Access Cover - 1350 x 600 Class B Pavermate® infill	82405	39.2
EzyBrixx Access Cover - 1350 x 600 Class B Rhinocast® infill	85465	88
EzyBrixx Access Cover - 1350 x 600 Class D Rhinocast® infill	89463	172
EzyBrixx Access Cover - 1350 x 600 Class B Rhinocast® Solid Top	Contact ACO	
EzyBrixx Access Cover - 1350 x 600 Class D Rhinocast® Solid Top	Contact ACO	

**Accessories**

Descriptions	Part No.
EzyBrixx Cable support (each)	142567
Universal Lifting Key	84306
Rhinocast®: Lifting key - Short handle (pair)	84654
Rhinocast®: Lifting key - Long handle (pair)	84854
4m eye to eye lifting slings (set of 4)	142565
Holesaw EzyBrixx: tungsten grit 30mm system - Short Hex	142760
Holesaw EzyBrixx: tungsten grit 65mm system - Short Hex	142761
Holesaw EzyBrixx: tungsten grit 70mm system - Short Hex	142762
Holesaw EzyBrixx: tungsten grit 90mm system - Short Hex	142763
Holesaw EzyBrixx: tungsten grit 120mm system - Short Hex	142764
Holesaw EzyBrixx: tungsten grit 160mm system - Short Hex	142765
Holesaw EzyBrixx: tungsten grit 30mm system -Short SDS	142766
Holesaw EzyBrixx: tungsten grit 65mm system -Short SDS	142767
Holesaw EzyBrixx: tungsten grit 70mm system - Short SDS	142768
Holesaw EzyBrixx: tungsten grit 90mm system - Short SDS	142769
Holesaw EzyBrixx: tungsten grit 120mm system - Short SDS	142770
Holesaw EzyBrixx: tungsten grit 160mm system - Short SDS	142771
Holesaw EzyBrixx: pilot key - 200mm long	142772
Holesaw EzyBrixx: pilot key - 40mm long drift key	142773
Short SDS adaptor	142774
Short HEX adaptor	142775
Long HEX adaptor	142776
Long SDS adaptor	142777
Universal Plug	84625

**Specifications**

The cable pit shall be ACO EzyBrixx® - Type 8: 1350mm x 600mm x 900mm (clear opening)

- with/without\* base
- complete with a bolt lockable Class B/D\* steel lid/access cover\*\* (AS 3996)

The cable pit shall have an overall depth of 900mm

The pit body shall be manufactured from modular rigid (twin wall) polypropylene components comprising an interlocking wedge system configured in 150mm high stacking units.

The pit is to be supplied assembled and installed in accordance with the manufacturer's installations.

\* delete as applicable

\* For access covers:

- specify: solid top or infill type
- specify: locking or non-locking
- Specify Pavermate® or Tilemate (Class B) or Rhinocast® (Class B, D) – visit <https://www.acoaccess.com.au/products/> for more info.
- Request manufacturer for a rebate drawing to determine levels

**ACO Pty Ltd**

**Australia**

**Ph: 1300 765 226**

[www.acoaus.com.au](http://www.acoaus.com.au)

[sales@acoaus.com.au](mailto:sales@acoaus.com.au)

©2019 ACO Pty Ltd. All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions are suitable. ACO Pty Ltd. pursues a policy of continuous product development and reserves the right to amend specifications without notice.

